

20 PROGRAMS
PROGRAMMI
PROGRAMAS

- SOFT VACUUM
- MARINATING FUNCTION
- VACUUM SENSOR



KONA

Machine dimensions Dimensioni macchina Dimensiones máquina	1890 x 1030 x 1000h mm
Weight Peso Peso	500 kg
Voltage Voltaggio Voltaje	220 V-50/60 Hz 3ph  400 V-50/60 Hz 3ph 
Consumption Consumo Consumo	5,5 - 9,0 kW
Chamber dimensions Dimensioni camera Dimensiones cámara	910 x 800 x 225h mm
Oil lubricated pump Pompa a bagno d'olio Bomba de baño de aceite	150 m³/h Busch®
Welding bar Barra saldante Barra de soldadura	(2X)  820/820 mm
Double seal bar ● Barra doppia saldatura Barra doble soldadura	 ●
Cut-off seal bar ● Barra taglio sfrido Barra con corte de bolsa	 ●
Bar with 8mm wide sealing ● Barra con saldatura larga 8mm Barra con soldadura de 8mm de ancho	 ●
Bi-active sealing bar ● Saldatura biattiva Soldadura biactiva	
Protective atmosphere (opt.) Atmosfera protettiva (opz.) Atmosfera protegida (opc.)	
Vacuum sensor ● Sensore di vuoto Sensor de vacío	
Marinating function ● Funzione marinatura Funcion de marinado	



Visita nuestra tienda online



Este equipo puede utilizar
Bolsas para vacío
LISAS O GOFRADAS



- ✓ Standard
- ✓ Standard (not combinable with biactive welding)
-  Available on request
- Special voltage price on demand
- Extra vacuum
- Non-cumulative options

Di serie
Di serie (non cumulabile con saldatura biattiva)
Disponibile su richiesta
Voltaggio speciale prezzo su richiesta
Extra vuoto
Opzioni non cumulabili

Estándar
Estándar (no combinable con soldadura biactiva)
Disponible bajo pedido
Voltaje especial precio a petición
Extra vacío
Opciones no acumulativas